

Cellular Jammers Technical Data

High Power

50W Output Power/Band

Model CCJ1690



General Description

19" RACK MOUNT

The CCJ1690 has been designed for blocking GSM cellular network and all kinds of cellular standards in the world.

The CCJ1690 is using state-of-art technology for maximum performance.

The unit controlled by Microprocessor for PLL programming.

The CCJ1690 transmits noise signal which cut-off all cellular communication between mobile phones and cellular cells.

The jamming radius depends on the strength signal in given area.

All cellular mobile in vicinity of CCJ1690 will be totally **BLOCKED** and will not be able to receive or dial outgoing calls.

When CCJ1690 effect the mobile the display will show "NO SERVICE".

PHANTOM TECHNOLOGIES LTD.

68 AMAL ST., PETAH-TIKVA, ISRAEL

TEL. +972-3-9215720 FAX. +972-3-9215434

Web-Site: www.phantom.co.il

Technical Specifications

RF Characteristics	
Output Power per band	50W (100W total)
Internal Modulation	FM Hopping frequency
Signal Source	PLL synthesized
Power Supply	24VDC regulated and 90-260VAC
Modules Per Unit	2 bands
Remote Control	2 Buttons (wired)
Antenna	External - Directional 14 dBi gain or 2dBi Omni-Directional Antenna outputs includes VSWR protector
Jamming Frequency Bands	Up to 3 Bands from the following
Frequency Bands	425-475 MHz 851/869-894 MHz 925/935-960 MHz 1805-1880 MHz 1930-1990 MHz 2110-2170 MHz
Air Interface Standards	Digital: IDEN, TDMA, CDMA, GSM, UMTS Analog: AMPS, MNT, N-AMPS, TACS
Physical Data	
Dimensions	500 x 430 x 180 mm
Weight	As per configuration
Environment of operation	
Operating Temperature	-10°C - +65°C
Humidity	5% - 90%
Optional Accessories	
Rechargeable Battery	75AH
Control Cable Via PC	RS232 – 9 pins CABLE

PHANTOM TECHNOLOGIES LTD.

68 AMAL ST., PETAH-TIKVA, ISRAEL

TEL. +972-3-9215720 FAX. +972-3-9215434

Web-Site: www.phantom.co.il