

Cellular Jammers Technical Data

Medium Power

15W Output Power/Band

Model CCJ800PL



General Description

The CCJ800PL has been designed for blocking GSM cellular networks and all kinds of cellular standards in the world.

The CCJ800PL is using state-of-art technology for maximum performance.

The unit controlled by Microprocessor for PLL programming.

The CCJ800PL transmits noise signal which cut-off all cellular communication between mobile phones and cellular cells.

The jamming radius depends on the strength signal in given area.

All cellular mobile in vicinity of CCJ800PL will be totally **BLOCKED** and will not be able to receive or dial outgoing calls.

When CCJ800PL effect the mobile the display will show "NO SERVICE".

PHANTOM TECHNOLOGIES LTD.

68 AMAL ST., PETAH-TIKVA, ISRAEL

TEL. +972-3-9215720 FAX. +972-3-9215434

Web-Site: www.phantom.co.il

Technical Specifications:

RF Characteristics	
Output Power per band	15W
Internal Modulation	FM Hopping frequency
Signal Source	PLL synthesized
Power Supply	110/220VAC or 24VDC regulated
Modules Per Unit	3 bands
Remote Control	Optional
Antennas	External 8 dBi gain Directional or Omni-Directional
Jamming Frequency Bands	Up to 5 bands of the following for one Pelican case
Frequency Bands	425-475 MHz 851/869-894 MHz 925/935-960 MHz 1805-1880 MHz 1930-1990 MHz 2110-2170 MHz
Air Interface Standards	Digital: IDEN, TDMA, CDMA, GSM, UMTS Analog: AMPS, MNT, N-AMPS, TACS
Physical Data	
Dimensions	380 x 280 x 160mm – for dual band unit
Weight	Approx. 10Kg - for dual band unit
Environment of operation	
Operating Temp.	-20°C - +65°C
Humidity	5% - 80%
Optional Accessories	
Rechargeable Battery	24V/9AH
Control Cable Via PC	Wired
DC-DC Converter	External 12-24VDC

PHANTOM TECHNOLOGIES LTD.

68 AMAL ST., PETAH-TIKVA, ISRAEL

TEL. +972-3-9215720 FAX. +972-3-9215434

Web-Site: www.phantom.co.il